Attorney docket: FSP0036

## **Claims**

5

protrudes.

What is claimed is:

1 1. A scaffold comprising: 2 a plurality of legs; and an expandable platform assembly supported by the legs, the platform 3 4 assembly comprising at least two shelves, at least one of the shelves sliding in a lengthwise direction in relation to the others in a 5 6 telescoping fashion. 2. The scaffold of claim 1, further comprising: 1 2 a first shelf comprising a first rail; 3 a second shelf comprising a second rail; and the first rail coupled to slide within the second rail, and the first shelf 4 coupled to slide under the second shelf. 5 3. The scaffold of claim 2, further comprising: 1 a rail lock coupled to the outer rail, the rail lock comprising a pin and a 2 3 spring. 4. The scaffold of claim 2, further comprising: 1 the inner rail comprising a flange to support the first shelf; 2 the outer rail comprising a flange to support the second shelf; and 3 the outer rail comprising a gap through which the flange of the inner rail 4

- 5. The scaffold of claim 4, further comprising: 1 at least one of the flange of the inner rail and the flange of the outer rail 2 comprising a plurality of posts to stabilize at least one of the first 3 and second shelves, respectively. 4 6. The scaffold of claim 2, further comprising: 1 a transition to alleviate the abruptness of an edge between the first and 2 second shelves. 3 1 7. The scaffold of claim 1, further comprising: 2 at least one leg comprising a rod; a spring to urge the rod through an aperture in a caster and into contact 3 with a wheel; and 4 the aperture formed to pass the rod in limited orientations of the rod with 5 respect to the caster. 6 8. The scaffold of claim 7, further comprising: 1 the rod comprising corners and the aperture comprising points. 2 9. The scaffold of claim 7, further comprising: 1 the rod comprising a handle positioned such that a worker on the platform 2 assembly may use the handle to lift the rod out of contact with the 3
  - 1 10. The scaffold of claim 8, further comprising:

4

wheel and clear of the aperture.

the rod comprising a substantially square cross section and the aperture comprising one of eight and sixteen points.

## Attorney docket: FSP0036

1	11. The scaffold of claim 1, further comprising:
2	an expandable safety rail.
1	12. A scaffold comprising:
2	at least one leg comprising a rod;
3	a spring to urge the rod through an aperture in a caster and into contact
4	with a wheel; and
5	the aperture formed to pass the rod in limited orientations of the rod with
6	respect to the caster.
1	13. The scaffold of claim 12, further comprising:
2	the rod comprising corners and the aperture comprising points.
1	14. The scaffold of claim 12, further comprising:
2	the rod comprising a handle positioned such that a worker on the platform
3	assembly may use the handle to lift the rod out of contact with the
4	wheel and clear of the aperture.
1	15. The scaffold of claim 13, further comprising:
2	the rod comprising a substantially square cross section and the aperture
3	comprising one of eight and sixteen points.